Rugged Tablet PC 7"



Product Features:

- 7" High Quality 1024 x 600 Resolution LED Panel
- Intel[®] Atom Dual Core N2600 1.6GHz with Intel[®] NM10 Chipset
- 1 x DDR3 SO-DIMM RAM 4GB (Wide Temperature)
- Meet MIL-STD-810G Shock, Vibration and Drop Standard
- Bulit-in 802.11 a/b/g/n Wifi card and Bluetooth 4.0 (Class II) Module
- 3100 mAh Li-ion 7.4V Battery x 2

Product Specifications:

- CMOS 2D barcode scanner (Reads 1D and 2D barcodes)
- Full QWERTY Keyboard (5 programmable function keys)
- CID2 (By Request)
- UHR RFID (By Request)





Main Unit

Docking (Optional)

System Specification	Processor	Intel® Atom™ Processor N2600 1.6 GHz
	System Memory	4GB DDR3 SO-DIMM RAM (Wide Temperature)
	Storage	64GB mSATA SSD (Wide Temperature, upgradable to 512GB)
	Operating System	Windows Embedded Standard WS7P
Display Specification	Size	7"
	Resolution	1024 x 600
	Brightness	900nit (typ.)
	Touch	4W Resistive Touch (GFG)
	Sensors	Light sensor for auto backlight adjustment Position sensor (accelerometer) for portrait or landscape screen orientation
Wireless Communication	Wireless	802.11 a/b/g/n WiFi Card (Cisco® Compatible Extensions (CCXv4)) Support Infrastructure and ad hoc (Client Mode)
	Bluetooth	Class 2 Bluetooth 4.0 (compliant 3.0 and 2.1 + EDR support)
	WWAN	Optional LTE (Sierra MC7304 or MC7354)
	GPS	Built-in Neo-6 GPS module
Mechanical and Environment	Dimensions (W x L x H)	229.75 x 183 x 54 mm
	Weight	1.43 kg
	Operation Temperature	-20°C to 60°C (AC mode <mark>)</mark> , -2 <mark>0°C to 50°C (Battery m</mark> ode)
	Operation Humidity	5~95% RH (non condensing)
	IP Proof	IP67 V S IT POSSIBLE
	Certifications	CE / FCC / UL
I/O Connectors	External I/O	1 x USB 2.0 A Type 1 x RS232
		1 x Headset jack
		1 x 2.5Ø DC Power Input
	Expansion Potrs (Pin Headers for I/O Customization)	1 x Micro SD card slot (up to 32GB)
		4 x USB 2.0
		1 x power output 5V 2A
		1 x VGA (SVGA Resolution)
		4 x RS-232

19V DC in

7 hours**

65W

Dimensions (Main unit with docking):


Power input

Adapter

Camera

Battery Operating Time








4. M9020 Quick Start Guide x 1

5. Manual & Driver CD x 1 Stylus Pen x1

7. Hand Strap

Order Information			
M9020	Basic		
M9020-LE	4G/LTE for Europe		
M9020-LA	4G/LTE for North America		




Power


Management

Field Service

Features











2M pixel camera front side; 5M rear camera with autofocus and flash light





- 1. Lock 2. RS-232 Connectors
- RJ-45 Connector
 USB Ports
- 5. Bare leads DC connector 6. Power Connector







Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information
Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.