

Especificações Técnicas

RJ45 Ports	01 10/100/1000TX Data Input Port 01 10/100/1000TX PoE + Data Output Port Forward, Half Duplex and Full Duplex
Forward & Filtering Rate	1,488,000pps (1000Mbps)
LED Indicator	PWR, PoE.
PoE	IEEE802.3at, LTPoE++ 60W 4 pair output power for LTPoE++ (60W) 2 pair output power for PoE+ (30W)
Input Power	48-57VDC (Terminal Block)
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%-95% (non-condensing)
Shell	IP40 Protection.
Installation	DIN-Rail / Wall-mount
Dimension WxDxH	96 x 80 x 31 mm
Regulatory Approvals	ISO 9001 EN 55022:2010+AC: 2011, ClassA EN 61000-3-2: 2006+A1: 2009+A2: 2009 EN 61000-3-3: 2013 EN 55024:2010 IEC 61000-4-2: 2008 (ESD) IEC 61000-4-3: 2010 (RS) IEC 61000-4-4: 2012 (EFT) IEC 61000-4-5: 2014 (Surge) IEC 61000-4-6: 2013 (CS) IEC 61000-4-8: 2009 (PFMF)
Waranty	5 years.

ANI-48-60W



CARACTERÍSTICAS GERAIS

- Support 60W LTPoE++ Power Sourcing Equipment
- Compatible IEEE802.3at PoE+
- Support 10/100/1000Base-TX
- Over Voltage Protection
- 5-Year Warranty

Modelos

Model	Description
ANI-48-60W	Hardened Gigabit Single-Port 60W PoE Injector
Mounting Options	Default DIN-Rail Bracket installed, Wall Mount Bracket is included.
Power Options	75W/1.6A 48VDC Power Supply. Open Wire for Terminal Block
	Power Supply is to be purchased separately.

Soluções de Redes Industriais
 IOT



Rua Dalcídio Jurandir 255
 Sala 123 - Barra da Tijuca
 Rio de Janeiro - RJ - 22631-250
 +55 21 2294-3931 ph/fax
 vendas@abovenet.com.br
 www.abovenet.com.br