

Especificações Técnicas	
Data Rate	1.25Gbps/1.063Gbps operation
Wave-Length	1550nm DFB laser and PIN photodetector for 60km transmission
Transmission Distance	60km transmission
Compliant with	SFP MSA and SFF-8472 with duplex LC receptacle
Digital Diagnostic Monitoring	Internal Calibration or External Calibration
Compatibility	RoHS
Single Power Supply	+3.3v
Operating Temperature	-40 to +85°C
Certifications	• CDRH 21 CFR 1040 annd Laser Notice No. 50 • EN 60825-1 : 2007 • EN 60825-2 : 2004 • EN 60950-1 : 2006 • RoHS Directive 2002/95/EC • EN 55022 : 2006+A1 : 2007 • EN 55024 : 1998+A1 : 2001+A2 : 2003
Waranty	5 years



CARACTERÍSTICAS GERAIS

- Data-rate of 1.25Gbps operation 02 1000 Base-FX (SC, ST) SFP Slot.
- 1550nm DFB laser
- Compliant with SFP MSA and SFF-8472 with duplex LC receptacle
- Digital Diagnostic Monitoring
- 60km transmission
- Compatible with RoHS

Modelos

Model	Description
ANM-125GL60-SFP	1550nm, 1.25Gbps, 60km, -40°C ~ +85°C, With Digital Diagnostic Monitoring