

ANM-125GM2-SFP



Especificações Técnicas	
Data Rate	1.25Gbps/1.063Gbps operation
Wave-Length	1310nm FP Laser Diode
Transmission Distance	2km transmission with 50/125µm or 62.5/125µm MMF
Compliant with	SFP MSA and SFF-8472 with duplex LC receptacle
Digital Diagnostic Monitoring	Internal Calibration or External Calibration
Compatibility	RoHS
Single Power Supply	+3.3v
Operating Temperature	0 to +70°C
Certifications	• CDRH 21 CFR 1040 annd Laser Notice No. 50 • EN 60825-1 : 2007 • EN 60825-2 : 2004 • EN 60950-1 : 2006 • RoHS Directive 2002/95/EC • EN 55022 : 2006+A1 : 2007 • EN 55024 : 1998+A1 : 2001+A2 : 2003
Waranty	5 years



CARACTERÍSTICAS GERAIS

- Data-rate of 1.25Gbps operation 02 1000 Base-FX (SC, ST) SFP Slot.
- 1310nm FP Laser Diode
- Compliant with SFP MSA and SFF-8472 with duplex LC receptacle
- Digital Diagnostic Monitoring
- 2km transmission
- Compatible with RoHS

Modelos

Model	Description
ANM-125GM2-SFP	1310nm, 1.25Gbps, 2km, 0°C ~ +70°C, With Digital Diagnostic Monitoring



Rua Dalcídio Jurandir 255
Sala 123 - Barra da Tijuca
Rio de Janeiro - RJ - 22631-250
+55 21 2294-3931 ph/fax
vendas@abovenet.com.br
www.abovenet.com.br

Soluções de Redes Industriais
IOT