

## Especificações Técnicas

RJ45 Ports	08 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Fiber Ports	02 1000BaseFX SFP (Dual Mode, Auto Detection)
MAC Table	16K
Buffer Memory	4M bits
PoE Power per Port	30W Max (IEEE802.3af/at)
Bandwidth	1Gbps
Max Packet Length	1,5M Bytes
LED Indicators	<ul style="list-style-type: none"> <li>Power1, Power2 Status</li> <li>Speed light: 100Mbps-always; 10Mbps-twinkle</li> <li>Link/Activity</li> </ul>
Input Power	<ul style="list-style-type: none"> <li>Phoenix terminal, DC seat</li> <li>DC 48-57V (Redundant Power Input)</li> </ul>
Power Consumption	<ul style="list-style-type: none"> <li>15W Max. (PoE not in use)</li> </ul>
Protection	<ul style="list-style-type: none"> <li>Input Overload – Automatic Resettable</li> <li>Reverse Polarity</li> <li>4KV Surge Protection</li> </ul>
Operating Temperature	-40°C to 80°C
Storage Temperature	-40°C to 80°C
Relative Humidity	5% to 95% non-condensing
Shell	IP40 Protection, Metal Case
Installation	DIN-Rail / Wall-mount
Dimension L x W x H	138mm x 106mm x 41mm
Management Features	<ul style="list-style-type: none"> <li>Redundant network: STP/RSTP</li> <li>Multicast: IGMP Snooping V1/V2</li> <li>VLAN: IEEE 802.1Q 4K VLAN, QinQ</li> <li>Link Aggregation: manual</li> <li>Management Function: CLI/WEB/SNMP</li> <li>Diagnostic Maintenance: Port mirroring, Ping</li> <li>Alarm management: 1-way relay alarm output, RMON, SNMP Trap</li> <li>Security: DHCP Snooping, User hierarchical management</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>FCC Part15 Subpart B Class A,</li> <li>EN55022:2010+AC: 2011, Class A</li> <li>IEC 61000-4-2: 2008 (ESD)</li> <li>IEC 61000-4-3: 2010 (RS)</li> <li>IEC 61000-4-4: 2012 (EFT)</li> <li>IEC 61000-4-5: 2014 (Surge)</li> <li>IEC 61000-4-6: 2013 (CS)</li> <li>IEC 61000-4-8: 2009 (PFMF)</li> <li>EN61000-4-11</li> </ul>
Collision	IEC60068-2-27
Drop	IEC60068-2-32
Vibration	IEC60068-2-6
Safety grade	EN60950-1
Waranty	5 years.

## ANS-7208GP-SFP



### CARACTERÍSTICAS GERAIS

- 08 10/100/1000 Base-Tx.
- 02 1000 BaseFX SFP
- Support 802.3at/af.
- IP40 Protection, Meta Shell
- Over Voltage Protection
- Reverse Polarity Protection
- Electric 4KV surge protection
- Broadcast storm suppression
- Data control Port-based ingress/egress speed limit

### Modelos

Model	Description
ANS-7208GP-SFP	Managed 8-Port 10/100/1000Base-T PoE + 2-Port 100/1000Base-X SFP Ethernet Switch
Power Options	<ul style="list-style-type: none"> <li>• 240W/5A 48VDC DIN-Rail Power Supply. Open Wire for Terminal Block.</li> <li>• Power Supply is to be purchased separately.</li> </ul>



Rua Dalcídio Jurandir 255  
Sala 123 - Barra da Tijuca  
Rio de Janeiro - RJ - 22631-250  
+55 21 2294-3931 ph/fax  
vendas@abovenet.com.br  
www.abovenet.com.br

## Soluções de Redes Industriais IOT