

Especificações Técnicas

RJ45 Ports	24 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Combo Ports	04 10/100/1000 TP/SFP
MAC Table	8K
Buffer Memory	4M bits
PoE Power per Port	30W Max (IEEE802.3af/at)
Bandwidth	1Gbps
Max Packet Length	10K Bytes
LED Indicators	<ul style="list-style-type: none"> • Power1, Power2 Status • Speed light: 100Mbps-always; 10Mbps-twinkle • PoE per Port Status • Link/Activity
Input Power	<ul style="list-style-type: none"> • Phoenix terminal, DC seat • AC 100-240V (Redundant Power Input)
Power Consumption	<ul style="list-style-type: none"> • 15W Max. (PoE not in use)
Protection	<ul style="list-style-type: none"> • Input Overload - Automatic Resettable • Reverse Polarity • 4KV Surge Protection
Operating Temperature	0°C to 50°C
Storage Temperature	-10°C to 70°C
Relative Humidity	5% to 95% non-condensing
Shell	Metal Case
Installation	Rack-mountable
Dimension L x W x H	440mm x 200mm x 45mm
Management Features	<ul style="list-style-type: none"> • Redundant network: STP/RSTP • Multicast: IGMP Snooping V1/V2 • VLAN: IEEE 802.1Q 4K VLAN, QINQ • Link Aggregation: manual • Management Function: CLI/WEB/SNMP • Diagnostic Maintenance: Port mirroring, Ping • Alarm management: 1-way relay alarm output, RMON, SNMP Trap • Security: DHCP Snooping, User hierarchical management
Certifications	<ul style="list-style-type: none"> • FCC Part15 Subpart B Class A, • EN55022:2010+AC: 2011, Class A • IEC 61000-4-2: 2008 (ESD) • IEC 61000-4-3: 2010 (RS) • IEC 61000-4-4: 2012 (EFT) • IEC 61000-4-5: 2014 (Surge) • IEC 61000-4-6: 2013 (CS) • IEC 61000-4-8: 2009 (PFMF) • EN61000-4-11
Collision	IEC60068-2-27
Drop	IEC60068-2-32
Vibration	IEC60068-2-6
Safety grade	EN60950-1
Waranty	2 years.

ANS-GP4M24G4-SFP



CARACTERÍSTICAS GERAIS

- 24 10/100/1000 Base-Tx.
- 04 10/100/1000 TX + 04 100/1000 SFP Combo
- Support 802.3at/af.
- Over Voltage Protection
- Reverse Polarity Protection
- Electric 4KV surge protection
- Broadcast storm suppression
- Data control Port-based ingress/egress speed limit

Modelos

Model	Description
ANS-GP4M24G4-SFP	Managed 24-Port 10/100/1000T 802.3at PoE + 4-Port TP/SFP Combo Ethernet Switch
ANS-GP4M24G4-SFP-SR	Managed 24-Port 10/100/1000T 802.3at PoE + 4-Port 100/1000 SFP Combo Ethernet Switch with Static Routing Function
Power Options	<ul style="list-style-type: none"> • Phoenix terminal, DC seat • AC 100-240V