

ANS-H204GP-SFP



Especificações Técnicas	
RJ45 Ports	04x 10/100/1000Base-TX PoE Auto-Negotiation MDI/MDI-X. Ports 01 e 02 Supports Hi-PoE 60W.
Fiber Ports	02x 1000Base-SFP.
Buffer Memory	4M
Bandwidth	128Gbps (non-blocking)
Packet Forwarding Rate	8.93Mbps@64bytes
MAC Address	8K MAC
LED Indicator	Running Light: SYS, Interface Light: LINK, PoE, Fiber: L/A
Operating Temperature	-40°C to 85°C (-40°F to 185°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%-95% (non-condensing)
Casing	IP40 Protection, Aluminum Case
Installation	DIN-Rail / Wall-mount
Dimensions (W×H×D)	165 x 148 x 54mm (WxDxH)
Input Power	120W/3A 48VDC DIN-Rail Power Supply. Open Wire for Terminal Block
MTBF	> 539608 hours
Management	WEB, CLI, TELNET, SSH, SNMP
Protocols	VLAN, IGMP, DHCP Snooping, LLDP, PoE+ Management, ARP, ACL, STP, RSTP, SNMP.
Certifications	UL 60950-1 EN61000-4-2 (ESD), Level 3 EN61000-4-3 (RS), Level 3 EN61000-4-4 (EFT), Level 3 EN61000-4-5 (Surge), Level 3 EN61000-4-6 (CS), Level 3 EN61000-4-8 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 FCC Part 15 Subpart B Class A, EN 55022 Class A IEC61000-6-2 EN50155, EN50121-4 NEMA TS-2
Waranty	5 years.



CARACTERÍSTICAS GERAIS

- 04 10/100/1000Base-Tx PoE
- Port 01 and 02 Supports Hi-PoE
- 02 1000Base-SFP Slot.
- 01 10/100/1000 Console Port
- Suports 802.3x
- gKb Jumbo Frame

Modelos	
Model	Description
ANS-H204GP-SFP	L2+ Network Managed 4-Port 10/100/1000T 802.3at PoE + 1-Port 10/100/1000T Console + 2-Port 1000X SFP Switch, Port 1-2 support PoE Power Output: 60W
SFP Options	SFP option. Please select your SFP on our SFP Options Page (Industrial SFP). SFP module is to be purchased separately.
Power Options	120W/3A 48VDC DIN-Rail Power Supply. Open Wire for Terminal Block. Power Supply is to be purchased separately.

Soluções de Redes Industriais IOT



Rua Dalcídio Jurandir 255
Sala 123 - Barra da Tijuca
Rio de Janeiro - RJ - 22631-250
+55 21 2294-3931 ph/fax
vendas@abovenet.com.br
www.abovenet.com.br