

Especificações Técnicas	
RJ45 Ports	24 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Fiber Ports	02 1000BaseX SFP or 04 1000BaseX SFP
Packet Buffer Memory:	2.75 Mbits
Bandith	52Gbps
Adresses MAC Table	8K MAC
Management	Web Interface
LED Indicator	Power, Network, PoE working status.
Operating Temperature	-20 ° to 55 ° C (-4°F to 131°F)
Storage Temperature	-20 ° to 75 ° C (-4°F to 167°F)
Relative Humidity	10%-90% (non-condensing)
Installation	Rack-Mount
Dimensions (W×H×D)	440 x 44.5 x 275mm
Maximum PoE Power	400W
PoE Port Power	25.5W
Input Power	100~240VAC (85~264VAC) Power Adapter
MTBF	> 190,000 hrs
Certifications	- FCC Part 15 Class B - CISPR22 (EN55022), Class B - VCCI Class B
Warranty	3 years.

CARACTERÍSTICAS GERAIS

- 24 10/100/1000 Base-Tx
- 02 or 04 1000 Base-X SFP Slot.
- Suporta 802.3x Controle de Fluxo
- Suporta 802.3af/at



Modelos	
Model	Description
ANS-M2024GPF-SFP	Managed 24-Port PoE Switch: 24x 10/100/1000M Ethernet ports + 2x or 4x Gigabit TP/SFP combo ports, and 1-24 ports supports IEEE802.3af POE international standard, each port power is 15.4W, whole power is 400W
ANS-M2024GPT-SFP	Managed 24-Port PoE Switch: 24x 10/100/1000M Ethernet ports + 2x or 4x Gigabit TP/SFP combo ports, and 1-24 ports supports IEEE802.3at POE international standard, each port power is 25.5W, whole power is 650W
SFP Options	SFP module is to be purchased separately