

Especificações Técnicas

RJ45 Ports	04 10/100/1000 Base-TX auto-negotiation MDI/MDI-X.
Fiber Ports	04 1000Base-FX (SC, ST, FC optional) SFP.
Packet Buffer Memory:	4 Mbits
Adresses MAC Table	8K MAC
LED Indicator	PWR, FX, ALM, Link/ACT.
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%~90% (non-condensing)
Casing	IP 40 Aluminum case
Installation	DIN-Rail / Wall-mount
Dimensions (W×H×D)	122 x 54 x 182 mm (L x W x H)
Input Power	12~48VDC , (4-pin Terminal Block)
MTBF	> 200,000 hrs
Protocols	<ul style="list-style-type: none"> • Redundant network: STP/RSTP • ARP • ICMP • TCP • DHCP • DNS • HTTP • Telnet • B-Ring
Management	CLI/WEB/SNMP
Certifications	ISO9001, CE, FCC, RoHS EMI <ul style="list-style-type: none"> • EN55022:2010+AC: 2011, Class A • EN 61000-3-2: 2006+A1: 2009+A2: 2009 • EN 61000-3-3: 2013 • EN55024:2010 EMS <ul style="list-style-type: none"> • EN61000-4-2(ESD) • EN61000-4-3(RS) • EN61000-4-4(EFT) • EN61000-4-5(Surge) • EN61000-4-6(CS) • EN61000-4-8(PFMF)
Waranty	5 years.



CARACTERÍSTICAS GERAIS

- 04 10/100/1000 Base-Tx
- 04 1000 Base-X SFP Slot.
- MAC Table 8k
- Suporta 802.3x Controle de Fluxo
- Suporta 802.3az (Energy Efficient Ethernet)
- Proteção Contra Sobretensão
- Proteção Contra Inversão de Polaridade

Modelos

Model	Description
ANS-IMCM404 G-SFP	L2+ 4-Port 10/100/1000T + 1-Port 10/100/1000T Console + 4-Port 100/1000X SFP Managed Switch
SFP Options	SFP module is to be purchased separately (purchased separately)
Power Options	24W/1A 24VDC DIN-Rail Power Supply. Open Wire for Terminal Block (purchased separately)