

Especificações Técnicas

RJ45 Ports	16 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Fiber Ports	04 100/1000BaseX SFP
Packet Buffer Memory:	4 Mbits
Bandith	1Gbps
Adresses MAC Table	8K MAC
Management	CLI/WEB/SNMP, and Primestone NIS management system
LED Indicator	Power, Network, PoE working status.
Operating Temperature	-40 ° to 80 ° °C
Storage Temperature	-40 ° to 85 ° °C
Relative Humidity	10%-90% (non-condensing)
Installation	Rack-Mount
Protection grade	IP 40 Aluminum Case
Dimensions (W×H×D)	130 x 70 x 160mm
PoE Port Power	30W
Input Power	48-57VDC Terminal block (Redudant power input)
MTBF	> 500,000 hrs
Management Features	<ul style="list-style-type: none"> • Redundant network: STP • EAPS/ERPS Multicast: IGMP Snooping V1/V2/V3 • GMRP VLAN: IEEE 802.1Q 4K VLAN, QINQ • Link Aggregation: manual / static / LACP • QOS: COS, DSCP, 8 queues, WRR/SP/WFQ scheduling, QOS Policy • Management Function: CLI/WEB/SNMP, and Primestone NIS management system • Diagnostic Maintenance: Port mirroring, Syslog, Ping • Alarm management: 1 way relay alarm output, RMON, SNMP Trap • Security DHCP Snooping, Option 82, 802.1X, User hierarchical management, ACL,DDOS, port based MAC filtering / binding • Data control: Port-based ingress/egress speed limit, Full duplex IEEE 802.3x, half duplex back-pressure flow control. Broadcast storm suppression, Unknown-Multicast suppression and Unknown-Unicast suppression.
Certifications	<ul style="list-style-type: none"> • FCC Part15 Subpart B Class A • EN61000-4-2(ESD) • EN61000-4-3(RS) • EN61000-4-6(CS) • EN61000-4-11 • IEC60068-2-32 • EN 55022 Class A • EN61000-4-5(Surge) • EN61000-4-4(EFT) • EN61000-4-8 • IEC60068-2-27 • IEC60068-2-6
Warranty	5 years.



CARACTERÍSTICAS GERAIS

- 16 10/100/1000 Base-Tx
- 04 100/1000 Base-X SFP Slot.
- Suporta 802.3x Controle de Fluxo
- Suporta 802.3af/at
- Electric 4KV surge protection
- Support IEEE802.3az

Modelos

Model	Description
ANS-M7416GP-SFP	Managed 16-Port 10/100/1000Base-T PoE + 4-Port 100/1000Base-X SFP Ethernet Switch
SFP Options	SFP module is to be purchased separately
Power Options	480W/10A 48VDC DIN-Rail Power Supply. Open Wire for Terminal Block. Power Supply is to be purchased separately

Soluções de Redes Industriais

IOT