

Especificações Técnicas

| | |
|-----------------------|---|
| RJ45 Ports | 08 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X. |
| Combo Ports | 02 1000BaseFX SFP (Dual Mode, Auto Detection) |
| MAC Table | 8K |
| Buffer Memory | 4M bits |
| PoE Power per Port | 30W Max (IEEE802.3af/at) |
| Bandwidth | 1Gbps |
| Max Packet Length | 10K Bytes |
| LED Indicators | <ul style="list-style-type: none"> • Power1, Power2 Status • Speed light: 100Mbps-always; 10Mbps-twinkle • Link/Activity |
| Input Power | AC 100-240V |
| Power Consumption | <ul style="list-style-type: none"> • 5W Max. (PoE not in use) |
| Protection | <ul style="list-style-type: none"> • Input Overload – Automatic Resettable • Reverse Polarity |
| Operating Temperature | -5°C to 50°C |
| Storage Temperature | -10°C to 70°C |
| Relative Humidity | 5% to 90% non-condensing |
| Shell | Metal Case |
| Installation | Wall-mountable |
| Dimension L x W x H | 249mm x 152mm x 45mm |
| Management Features | <ul style="list-style-type: none"> • Redundant network: STP/RSTP • Multicast: IGMP Snooping V1/V2 • VLAN: IEEE 802.1Q 4K VLAN, QinQ • Link Aggregation: manual • Management Function: CLI/WEB/SNMP • Diagnostic Maintenance: Port mirroring, Ping • Alarm management: 1-way relay alarm output, RMON, SNMP Trap • Security: DHCP Snooping, User hierarchical management |
| Certifications | <ul style="list-style-type: none"> • FCC Part15 Subpart B Class A, • EN55022:2010+AC: 2011, Class A • IEC 61000-4-2: 2008 (ESD) • IEC 61000-4-3: 2010 (RS) • IEC 61000-4-4: 2012 (EFT) • IEC 61000-4-5: 2014 (Surge) • IEC 61000-4-6: 2013 (CS) • IEC 61000-4-8: 2009 (PFMF) • EN61000-4-11 |
| Collision | IEC60068-2-27 |
| Drop | IEC60068-2-32 |
| Vibration | IEC60068-2-6 |
| Safety grade | EN60950-1 |
| Waranty | 2 years. |

ANSM82GPSFP



CARACTERÍSTICAS GERAIS

- 08 10/100/1000 Base-Tx.
- 02 1000 BaseFX SFP Combo
- Support 802.3at/af.
- Over Voltage Protection
- Reverse Polarity Protection
- Broadcast storm suppression
- Data control Port-based ingress/egress speed limit

Modelos

| Model | Description |
|---------------|--|
| ANSM82GPSFP | Managed 8-Port 10/100/1000T 802.3at PoE + 2-Port 100/1000M SFP Ethernet Switch |
| Power Options | Redundant power input AC 100-240V |