

## Especificações Técnicas

RJ45 Ports	24 10/100/1000 Base-TX auto-negotiation MDI/MDI-X.
Fiber Ports	04 1000BaseX SFP
Packet Forwarding Rate	95.232Mbps
Bandwidth	56Gbps
Flash Memory	8MB
RAM Memory	128MB
Addresses MAC Table	16K MAC
Protocols	STP, RSTP, MSTP, PVST/PVST+, IGMP v1/v2/v3, MLDv2, DVMRP, GMRP, LACP, RIP v1/v2, OSPFv2, BEIGRP (compatible with Cisco EIGRP), BGPv4, ISIS, BGP, VRRP, HSRP (Hot Standby Router Protocol), RADIUS, TACACS+, WRED, WFQ.
Management	Web Interface, SNMP v1/v2/v3, RMON (1,2,3,9 Group), Telnet, Cluster Management, SSH, PDP (Compatible with Cisco CDP).
LED Indicator	Power, Network, working status.
Operating Temperature	0 ° to 50 ° C
Storage Temperature	-40 ° to 70 ° C
Relative Humidity	0%-90% (non-condensing)
Installation	Rack-Mount
Dimensions (W×H×D)	440 x 230 x 44mm
Power	80W
Input Power	AC 110-240V adaptive, 47-63Hz, 1A/230V, RPS power hot backup
MTBF	> 190,000 hrs
Certifications	<ul style="list-style-type: none"> <li>FCC Part 15 Class B</li> <li>CISPR22 (EN55022), Class B</li> <li>VCCI Class B</li> </ul>
Warranty	3 years.

## CARACTERÍSTICAS GERAIS

- 24 10/100/1000 Base-Tx
- 04 1000 Base-X SFP Slot.
- Suporta 802.3x Controle de Fluxo
- RMON
- RADIUS/TACACS+



## Modelos

Model	Description
ANS-M2424G-SFP	Managed 24-Port Switch: 24x 10/100/1000M Ethernet ports + 4x Gigabit SFP ports.
SFP Options	SFP module is to be purchased separately