

## Especificações Técnicas

RJ45 Ports	24 10/100/1000Base-TX auto-negotiation MDI/MDI-X.
Fiber Ports	04 1000Base-X Combo SFP.
Transmission Distance	Depending on SFP
Packet Buffer	4Mbits
MAC Address Table	8K
Bandwidth	1Gbps
LED Indicator	Link/Act RJ45 and Fiber, PWR
Input Power	Phoenix terminal, DC seat - AC 100~240V
Overload Protection	Yes
Power Reverse	Support
Operating Temperature	0°C~50°C
Storage Temperature	-10°C~70°C
Relative Humidity	5%-90% (non-condensing)
Shell	IP30 Protection, Metal Case
Installation	19" 1U rack
Dimension L×W×H	440mm*200mm*45mm
EMI	FCC Part15 Subpart B Class A, EN 55022 Class A
EMS	<ul style="list-style-type: none"> <li>• EN61000-4-2(ESD),</li> <li>• EN61000-4-3(RS),</li> <li>• EN61000-4-4(EFT),</li> <li>• EN61000-4-5(Surge),</li> <li>• EN61000-4-6(CS),</li> <li>• EN61000-4-8,</li> <li>• EN61000-4-11</li> </ul>
Management Features	<ul style="list-style-type: none"> <li>• <b>Redundant Network:</b> STP/RSTP</li> <li>• <b>Multicast:</b> IGMP Snooping V1/V2</li> <li>• <b>VLAN:</b> IEEE 802.1Q 4K VLAN, QINQ</li> <li>• <b>Link Aggregation:</b> manual</li> <li>• <b>Management Function:</b> CLI/WEB/SNMP</li> <li>• <b>Diagnostic Maintenance:</b> Port mirroring, Ping</li> <li>• <b>Alarm Management:</b> 1-way relay alarm output, RMON, SNMP Trap</li> <li>• <b>Security:</b> DHCP Snooping, User hierarchical management</li> <li>• <b>Data Control Port-based</b> ingress/egress speed limit, Full duplex IEEE 802.3x, half duplex back-pressure flow control.</li> <li>• <b>Broadcast Storm Suppression.</b> Unknown-Multicast suppression and Unknown-Unicast suppression</li> </ul>
Collision	IEC 60068-2-27
Drop	IEC 60068-2-32
Vibration	IEC 60068-2-6
Safety Grade	EN60950-1
Waranty	3 years.

## ANS-M28G4F



### CARACTERÍSTICAS GERAIS

- 24 10/100/1000 Base-Tx
- 04 1000Base-X Combo SFP Slot.
- Power Reverse - Supports
- STP/RSTP
- IP30 Protection, Meta Shell
- Over Voltage Protection
- IGMP, SNMP, VLAN and RMON
- Support Broadcast Storm Shield

### Modelos

Model	Description
ANS-M28G4F	Managed 24-Port 10/100/1000T + 4-Port 100/1000 SFP Combo Ethernet Switch.
ANS-M28G4F-SR	Managed 24-Port 10/100/1000T + 4-Port 100/1000 SFP Combo Ethernet Switch with <b>Static Routing Function</b>
SFP Options	SFP module is to be purchased separately
Power Options	Phoenix terminal, DC seat AC 100~240V

Soluções de Redes Industriais  
IOT