

Especificações Técnicas	
RJ45 Ports	24 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Fiber Ports	02 1000Base-FX Combo (SC,ST,FC optional) SFP
Adresses MAC Table	8K MAC
Console Port	RSS232, RJ45
LED Indicator	Power, Network, PoE working status.
Operating Temperature	-20 ° to 55 ° C (-4°F to 131°F)
Storage Temperature	-20 ° to 75 ° C (-4°F to 167°F)
Relative Humidity	10%-90% (non-condensing)
Shell	IP30, Metal Case
Installation	Rack-Mount
Dimensions (W×H×D)	440 x 275 x 44.5mm
Maximum PoE Power	600W
PoE Port Power	15.4W
Input Power	110~220VDC (100~300VDC) Or 100~240VAC (85~264VAC) Conector: 3 bits terminal block
MTBF	> 200,000 hrs
Certifications	FCC Part 15, CISPR(EN55022)class EN61000-4-2(ESD), Level 3 EN61000-4-3(RS), Level 3 EN61000-4-4(EFT), Level 3 EN61000-4-5(Surge), Level 3 EN61000-4-6(CS), Level 3 EN61000-4-8, 100A/m EN61000-4-12
Shock	IEC 60068-2-27
Free Fall	IEC 60068-2-32
Vibration	IEC 60068-2-6
Waranty	3 years.

ANS-2024GP



CARACTERÍSTICAS GERAIS

- 08 10/100/1000 Base-Tx
- 02 1000 Base-FX (SC, ST) SFP Slot.
- Fonte Redundante.
- Suporta 802.3x Controle de Fluxo
- Suporta 802.3af/at
- Proteção Contra Sobretensão
- Proteção Contra Inversão de Polaridade

Modelos

Model	Description
ANS-2024GPF-SFP	Unmanaged 24-Port PoE Switch: 24x 10/100/1000M Ethernet ports + 2x Gigabit TP/SFP combo ports, and 1-24 ports supports IEEE802.3af POE international standard, each port power is 15.4W, whole power is 400W
ANS-2024GPT-SFP	Unmanaged 24-Port PoE Switch: 24x 10/100/1000M Ethernet ports + 2x Gigabit TP/SFP combo ports, and 1-24 ports supports IEEE802.3at POE international standard, each port power is 25.5W, whole power is 650W
SFP Options	SFP module is to be purchased separately



Rua Dalcídio Jurandir 255
Sala 123 - Barra da Tijuca
Rio de Janeiro - RJ - 22631-250
+55 21 2294-3931 ph/fax
vendas@abovenet.com.br
www.abovenet.com.br

Soluções de Redes Industriais IOT