

Especificações Técnicas

RJ45 Ports	08 10/100/1000 Base-TX PoE auto-negotiation MDI/MDI-X.
Uplink Ports	02 10/100/1000 Base-TX
MAC Table	8K
PoE Power per Port	30W Max (IEEE802.3af/at)
Bandwidth	20 Gbps (non-blocking)
Max Packet Length	10K Bytes
LED Indicators	<ul style="list-style-type: none"> Green light: Ethernet Red light: PoE
Input Power	AC 110-260V
Power Consumption	<ul style="list-style-type: none"> 150W Max. (PoE in use)
Operating Temperature	-20°C to 55°C
Storage Temperature	-40°C to 80°C
Relative Humidity	5% to 90% non-condensing
Shell	Metal Case
Installation	Wall-mountable
Dimension L x W x H	220mm x 160mm x 35mm
Certifications	<ul style="list-style-type: none"> CE/LVD EN60950 RoHS FCC FCC Part 15 Class B; VCCI Class B; EN 55022 (CISPR 22), Class B
Waranty	2 years.

ANS-208GP



CARACTERÍSTICAS GERAIS

- 08 10/100/1000 Base-Tx.
- 02 10/100/1000 Base-Tx Uplink
- Support 802.3at/af.
- MAC Table 8K
- Bandwidth 20 Gbps (non-blocking)

Modelos

Model	Description
ANS-208GP	10-Ports 10/100/100M switch with 8 PoE ports, IEEE 802.3af/at; PoE Power Output: 15,4Watts/30Watts per port. Total power budget 120Watts
Power Options	Redundant power input AC 110-260V