

## Especificações Técnicas

|                       |   |
|-----------------------|---|
| RJ45 Ports            | 04 10/100 Base-TX PoE auto-negotiation MDI/MDI-X.   |
| Fiber Ports           | 01 10/100 Base-FX SFP   |
| MAC Table             | 1K  |
| PoE Power per Port    | 30W Max (IEEE802.3af/at)  |
| Forward Rate          | 14,880pps (10Mbps)<br>148,800pps (100Mbps)  |
| Buffer Memory         | 512K Bits   |
| LED Indicators        | <ul style="list-style-type: none"> <li>• Link/Activity (Ethernet Port)</li> <li>• Link/Activity (SFP)</li> <li>• Power Status</li> </ul>                      |
| Input Power           | 48-57 VDC   |
| Power Consumption     | <ul style="list-style-type: none"> <li>• 135W Max. (PoE in use)</li> <li>• 5W (PoE not in use)</li> </ul>   |
| Operating Temperature | -40°C to 80°C   |
| Storage Temperature   | -40°C to 85°C   |
| Relative Humidity     | 5% to 90% non-condensing  |
| Shell                 | Metal Case  |
| Installation          | DIN-Rail / Wall-mount   |
| Dimension W x D x H   | 134mm x 101mm x 28mm  |
| Certifications        | <ul style="list-style-type: none"> <li>• ISO9001</li> <li>• EN55022 Class A, FCC part 15 Class A</li> <li>• Surge Protection:</li> <li>• RJ45: 1KV</li> </ul> |
| Waranty               | 5 years.  |

## ANS-IMC1400P-SFP



### CARACTERÍSTICAS GERAIS

- 04 10/100 Base-Tx.
- 01 10/100 Base-FX SFP
- Support 802.3af/at.
- MAC Table 1K
- Power Input Overload
- Reverse Polarity

### Modelos

| Model            | Description   |
|------------------|---|
| ANS-IMC1400P-SFP | 4-Ports 10/100 Base-TX PoE ports, IEEE 802.3af/at; PoE Power Output: 15,4Watts/30Watts per port. 1 Port FX SFP 10/100 |
| Power Options    | 48-57 VDC Terminal Block  |