

Especificações Técnicas	
RJ45 Ports	05 10/100Base-T auto-negotiation MDI/MDI-X.
Forward & Filtering Rate	14,880pps (10Mbps) 148,800pps (100Mbps)
LED Indicator	PWR1, PWR2, Link/ACT.
Input Power	12~58VDC , Redundant Power (6-pin Terminal Block)
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%~95% (non-condensing)
Shell	IP40 Protection.
Installation	DIN-Rail / Wall-mount
Dimension W×H×D	50 x 108 x 139 mm
Regulatory Approvals	ISO 9001 EN 55022:2010+AC: 2011, ClassA EN 61000-3-2: 2006+A1: 2009+A2: 2009 EN 61000-3-3: 2013 EN 55024:2010 IEC 61000-4-2: 2008 (ESD) IEC 61000-4-3: 2010 (RS) IEC 61000-4-4: 2012 (EFT) IEC 61000-4-5: 2014 (Surge) IEC 61000-4-6: 2013 (CS) IEC 61000-4-8: 2009 (PFMF)
Waranty	5 years.

ANS-005



CARACTERÍSTICAS GERAIS

- 05 10/100Base-T
- Support 802.3x Flow Control
- IP40 Protection
- Over Voltage Protection
- Redundant Power Inputs (6-pin Terminal Block)

Modelos	
Model	Description
ANS-005	Industrial 5-port 10/100BASE-T Ethernet Switch
Mounting Options	Default DIN-Rail Bracket installed, Wall Mount Bracket is included.
Power Options	24W/1A 24VDC DIN-Rail Power Supply. Open Wire for Terminal Block. .
	Power Supply is to be purchased separately.



Rua Dalcídio Jurandir 255
Sala 123 - Barra da Tijuca
Rio de Janeiro - RJ - 22631-250
+55 21 2294-3931 ph/fax
vendas@abovenet.com.br
www.abovenet.com.br

Soluções de Redes Industriais
IOT