

Especificações Técnicas

RJ45 Ports	16 10/100Base-T auto-negotiation MDI/MDI-X.
Forward & Filtering Rate	14,880pps (10Mbps) 148,800pps (100Mbps)
MAC Table	8K
Packet Buffer	1Mbit
LED Indicator	PWR1, PWR2, Link/ACT.
Input Power	18-36VDC , Redundant Power (6-pin Terminal Block) Redundant Protection (Support)
Overload Current Protection	Support
Reverse Polarity Protection	Support
Operating Temperature	-40°C to 85°C
Storage Temperature	-45°C to 85°C
Relative Humidity	5%-95% (non-condensing)
Shell	IP40 Protection.
Installation	DIN-Rail / Wall-mount
Dimension W×H×D	118 x 160 x 140 mm
Regulatory Approvals	EN 55022:2010+AC: 2011, ClassA IEC 61000-4-2: 2008 (ESD) IEC 61000-4-3: 2010 (RS) IEC 61000-4-4: 2012 (EFT) IEC 61000-4-5: 2014 (Surge) IEC 61000-4-6: 2013 (CS) IEC 61000-4-8: 2009, Level 5 Shock: IEC 60068-2-27 Free Fall: IEC 60068-2-32 Vibration: IEC 60068-2-6 Industry: IEC 61000-6-2 Rail: EN50155, EN50121-4 Traffic: NEMA TS-2 FCC, CE, RoHS Approvals
Waranty	5 years.



CARACTERÍSTICAS GERAIS

- 16 10/100Base-T
- Support 802.3x Flow Control
- IP40 Protection
- Over Voltage Protection
- Broadcast Storm Protection
- Redundant Protection
- Reverse Polarity Protection

Modelos

Model	Description
ANS-IES016	Industrial 16-port 10/100BASE-T Ethernet Switch
Mounting Options	Default DIN-Rail Bracket installed, Wall Mount Bracket is included.
Power Options	0.5A 24VDC DIN-Rail Power Supply. Open Wire for Terminal Block. . Power Supply is to be purchased separately.