

ANS-104

Especificações Técnicas	
RJ45 Ports	04 x 10/100Base-TX Auto-Negociation MDI/MDI-X.
Fiber Ports	01 x 100Base-FX (SC, ST, FC optional) SFP.
Buffer Memory	512K bits
MAC Address	1K MAC
LED Indicator	PWR, RUN and FX Link/ACT.
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%-95% (non-condensing)
Casing	IP40 Protection, Aluminum Case
Installation	DIN-Rail / Wall-mount
Dimensions (W×H×D)	50 x 139 x 108mm
Input Power	12~58VDC, Redundant Power (6-Pin Terminal Block)
MTBF	> 200,000 hrs
Certifications	UL 60950-1 EN61000-4-2 (ESD), Level 3 EN61000-4-3 (RS), Level 3 EN61000-4-4 (EFT), Level 3 EN61000-4-5 (Surge), Level 3 EN61000-4-6 (CS), Level 3 EN61000-4-8 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 FCC Part 15 Subpart B Class A, EN 55022 Class A IEC61000-6-2 EN50155, EN50121-4 NEMA TS-2
Waranty	5 years.



CARACTERÍSTICAS GERAIS

- 04 10/100Base-Tx
- 01 100Base-FX (SC, ST, FC) SFP Slot.
- Suporta 802.3x Controle de Fluxo
- 9Kb Jumbo Frame

Modelos	
Model	Description
ANS-104	Industrial Ethernet Switch: 4-Port 10/100Base-TX + 1-Port 100Base-FX Fiber, Multimode, Dual Fiber, SC, 2KM
ANS-104-20	Industrial Ethernet Switch: 4-Port 10/100Base-TX + 1-Port 100Base-FX Fiber, Single Mode, Dual Fiber, SC, 20KM
ANS-104S-20	Industrial Ethernet Switch: 4-Port 10/100Base-TX + 1-Port 100Base-FX Fiber, Single Mode, Single Fiber, SC, 20KM
ANS- 104F-20	Industrial Ethernet Switch: 4-Port 10/100Base-TX + 1-Port 100Base-FX Fiber,Single Mode, Single Fiber, FC, 20KM
ANS-104-SFP	Industrial 4-port 10/100BASE-T + 1-port 100BASE SFP Ethernet Switch
SFP Options	SFP module is to be purchased separately
Power Options	24W/1A 24VDC Power Supply. Open Wire for Terminal Block; Power Supply is to be purchased separately.