

IES208



CARACTERÍSTICAS GERAIS

- 08 10/100 Base-Tx
- 02 100 Base-FX (SC, ST) SFP Slot.
- Fonte Redundante.
- Suporta 802.3x Controle de Fluxo
- Proteção Contra Sobretensão
- Proteção Contra Inversão de Polaridade

Especificações Técnicas

RJ45 Ports	08 10/100 Base-TX PoE auto-negotiation MDI/MDI-X.
Fiber Ports	02 100 Base-FX (SC, ST, FC optional) SFP.
Packet Buffer Memory:	512 Kbits
Forward & Filtering Rate	14,880pps (10mb) and 148,800pps (100mb)
Adresses MAC Table	1K MAC
LED Indicator	PWR1, PWR2, FX1,FX2, SYS, Link/ACT.
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Relative Humidity	5%-95% (non-condensing)
Casing	Metal Case
Installation	DIN-Rail / Wall-mount
Dimensions (W×H×D)	50 x 108 x 139 mm
Input Power	12~58VDC , Redundant Power (6-pin Terminal Block)
MTBF	> 200,000 hrs
Certifications	ISO9001 EN55022:2010+AC: 2011, ClassA EN 61000-3-2: 2006+A1: 2009+A2: 2009 EN 61000-3-3: 2013 EN55024:2010 IEC 61000-4-2: 2008 (ESD) IEC 61000-4-3: 2010 (RS) IEC 61000-4-4: 2012 (EFT) IEC 61000-4-5: 2014 (Surge) IEC 61000-4-6: 2013 (CS) IEC 61000-4-8: 2009 (PFMF)
Waranty	5 years.

Modelos

Model	Description
LNK-IES208G	Industrial Ethernet Switch: 8-Port 10/100Base-TX + 2-port 100BASE-FX Fiber, Multimode, Dual Fiber, SC, 2KM
LNK-IES208-20	Industrial Ethernet Switch: 8-Port 10/100Base-TX + 2-port 100BASE-FX Fiber, Single Mode, Dual Fiber, SC, 20KM
LNK-IES208S-20	Industrial Ethernet Switch: 8-Port 10/100Base-TX + 2-port 100BASE-FX Fiber, Single Mode, Single Fiber, SC, 20KM
LNK-IES208F-20	Industrial Ethernet Switch: 8-Port 10/100Base-TX + 2-port 100BASE-FX Fiber, Single Mode, Single Fiber, FC, 20KM
LNK-IES208-SFP	Industrial 8-port 10/100 BASE-T + 2-port 100BASE SFP Ethernet Switch
SFP Options	SFP module is to be purchased separately
Power Options	24W/1A 24VDC DIN-Rail Power Supply. Open Wire for Terminal Block